



- NOTES:**
1. CLEAN-OUT SHALL BE INSTALLED BY THE BUILDER IN ACCORDANCE WITH STANDARD PLUMBING CODE.
 2. LOCATE SINGLE LATERAL AS CLOSE TO LOT LINE AS POSSIBLE, 25' MAXIMUM.
 3. INVERT OF SERVICE LATERAL SHALL NOT ENTER SEWER MAIN BELOW SPRING LINE.
 4. SERVICE LATERALS SHALL HAVE A MINIMUM 18" OF COVER BETWEEN R/W TIE-IN AND BUILDING.
 5. INDENT CURB WITH 'S' AT EACH SEWER SERVICE LOCATION.
 6. ROTATE BENDS AS REQUIRED TO ALIGN SERVICE BRANCH WITH THE SERVICE PIPE.
 7. ALL SERVICE LATERAL LOCATIONS SHALL BE APPROVED BY THE CITY.

REFER TO APPLICABLE PIPE FOUNDATION

CITY OF NORTH MIAMI BEACH PUBLIC UTILITIES DEPARTMENT		
SHALLOW SERVICE LATERAL DETAIL		
11/18/2015	A.D.V.	K.L.R.
Date	Revisions	Appr. by
Date: July 2000	Dwg: F205	Fig: 435